# **QiCR3600M**™ Innovative Computed Radiography



HIGHER RESOLUTION

LOWER DOSE



16 | Bit Resolution

35 | Plates Per/Hr

**78** | lbs

### **Stay** Competitive | **Improve** Patient Care | **Innovate** Imaging Workflow

Women's health is in the center of development efforts at iCRco. The **iCR3600M\*** integrates seamlessly into the existing workflow. **iCR3600M\*** is affordable and eliminates the need for replacing the existing X-ray room equipment while being ultra precise.

Physicians can achieve amazing workflow at a much lower cost with its integrated pairing with the robust and feature-rich image processing **XC™** software. **XC** provides superior quality images every time with an option to further manipulate the images.



## ICR | 3600M

**Image Capture Review** 

## **IMAGE**

#### 3600M | MAMMOGRAPHY

**iCR 3600M** is a scalable design that allows for the highest efficiency **Crystal IP** phosphor screens, 16 Bit available gray scale, and upgradable features that provide users with stunning 20 lp/mm maximum resolution.

## **CAPTURE**

#### **XC | ACQUISITION**

**XC** touchscreen acquisition with ICE-M Enhancement Processing provides all-new features including, "Image Display State" to ensure balanced presentation of both soft tissue, overlapping bone structures, and automatic analysis of image characteristics to optimize processing.

## **REVIEW**

#### **CLARITY PACS**

Our fully web-enabled and integrated PACS solutions help transition your practice into a safe, secure, and filmless environment.

Clarity PACS™ supports all your current and future imaging needs.

icrco.com











Although computed radiography technology has been widely accepted, other major manufacturers follow the same pattern of removing the costly phosphor plates and running them through rollers in their CR readers. iCRco has re-invented how CR technology works with 

True Flat Scan Path™. This technology ensures the phosphor plate never leaves the cassette to avoid any plate handling, damage or wear during the scan process.

#### iCR3600M Specifications\*

| Micron Spot Size                         | Pixels Per mm | Dots Per Inch (DPI) | Line Pairs Per mm |
|--|---------------|---------------------|-------------------|
| 50                                       | 20            | 508                 | 10                |
| 100                                      | 10            | 254                 | 5                 |
| THE ICOSCOOM CARTILIDES AT 15 MEGADIVELS |               |                     |                   |

| Grayscale resolution | 16 bits/pixel source file, 65536 shades of gray   |  |  |
|----------------------|---|--|--|
| Image access time    | 60 seconds (average mixed plates)   |  |  |
| Plate throughput     | 35 plates per hour mixed cassette sizes   |  |  |
| Cassette sizes       | $14'' \times 17'' (35 \times 43 \text{ cm})$ , $14'' \times 14'' (35 \times 35 \text{ cm})$ , $10'' \times 12'' (25 \times 30 \text{ cm})$ , $8'' \times 10''$ (20 x 25 cm) $24 \times 30 \text{ cm}$ , $18 \times 24 \text{ cm}$ High resolution Mammography plates accepted. Odd plates and flexible plates using glass cassette system are accepted. |  |  |
| Weight               | 78 lbs (35 kg)  |  |  |
| Dimensions           | W44" x D12" x H23" (W112 x D31 x H59 cm), Wall mountable  |  |  |
| Power source         | 100-240V AC/ 2.5A max; 47-63Hz (Universal power supply)   |  |  |
| Heat generation      | Typical 125W, maximum 330W  |  |  |
| Operating conditions | Temperature; 0-40°C/32-105°F, temperature change: $0.5$ °C/min, humidity: 15%-95% RH, magnetic fields: max 1260 $\mu$ T (in conformance with EN 61000-4-8: level 3), 10 A/m   |  |  |

<sup>\*</sup> Specifications are subject to change without notice. Processing and display time dependent on processor speed, RAM disk access time, and video card.



Components are made from 98% recyclable parts • iCRco is an ISO 13485 certified company • U.S. and international patents granted • Additional patents pending • FDA 510 (K) Cleared

• Medical CE mark C € 0086

© 2014 iCRco. All rights reserved. "True Flat Scan Path" and "XC" are registered trademarks of iCRco. BR0101614BUS

#### XC<sup>™</sup> Acquisition Software Features

XC - Intuitive touchscreen acquisition

ICE-M Processing - Automated image characteristics analysis for maximum image enhancement

Image Display State: Automated enhancement of image display at the point of acquisition

Smart search, sort, and filter options

Integration with front office management systems like RIS and EMR

Full set of annotation and measurement tools

User-preferred settings and privileges

#### **Outer Dimensions**



